

CENTOR First Force measurement




Accurate and simple force measurement

Simple and yet complete, the CENTOR First uses efficient technology to simplify force measurements, in tension and compression. A big display shows the force measured in tension or compression in the unit selected by the operator: newtons, kilograms or pounds. The bar graph completes the measurement. The 3 keys make it very easy to use this force gauge and access the essential functions: measurement of the peak tension or compression value, resetting to zero and changing the measuring units. It is an ideal tool for basic tests during production. Its metal casing, protected by an elastomer overmould, gives it exceptional strength. The internal sensor stands up to an overload of 200% of its maximum capacity. Simple, precise, robust, supplied with its own carrying case, mains adaptor and certificate. Ready for use, it is the basic tool for force measurement.

Specifications

| FEATURES | CENTOR FIRS |
|---|-------------|
| Accuracy | 0,25 % FS |
| Resolution | 0,01 lb |
| Data rate | I,000 Hz |
| Sensor protected from overload | 200% FS |
| Units | N, Lb, Kg |
| Auto-off | 15 minutes |
| Bar Graph | v |
| Peak in tension and compression | v |
| Tare | v |
| Reversible display | 180° |
| Operates on rechargeable batteries | v |
| 8 hours of operations without recharging | v |
| Fast charge | v |
| Low battery indicator | v |
| Metal casing and protective elastomer overmould | v |
| Threaded fixing holes on the back | × |
| RS232 output | |





2.25 in 2 x 10-32

2.25 ir

.3.35

Value displayed

Models and capacities

| MODELS | CAPACITIES | ACCURACY | RESOLUTIONS |
|---------------|------------|----------|-------------|
| CNR FT 100 | 20 lb | 0.05 lb | 0.01 lb |
| CNR FT 250 | 50 lb | 0.12 lb | 0.01 lb |
| CNR FT 500 | 100 lb | 0.25 lb | 0.01 lb |
| CNR FT 100 XZ | 20 lb | 0.05 lb | 0.01 lb |
| CNR FT 250 XZ | 50 lb | 0.12 lb | 0.01 lb |
| CNR FT 500 XZ | 100 lb | 0.25 lb | 0.01 lb |



Our force gauges are delivered in a carrying case with power supply, certificate of calibration and accessories (hook, plate diameter 3/4 in, rod)







Certified ISO 9001:2008 COM-TEN Industries 6405 49th Street North Pinellas Park, FL, 33781 - USA sales@com-ten.com • www.com-ten.com Tel. : +1 727-520-1200 • Fax : +1 727-520-0299

0.5 in

र्त

l :0.27